

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
22 March 2001 (22.03.2001)

PCT

(10) International Publication Number  
WO 01/19430 A1(51) International Patent Classification<sup>7</sup>: A61M 1/28

(21) International Application Number: PCT/SE00/01772

(22) International Filing Date:  
14 September 2000 (14.09.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
9903331-8 16 September 1999 (16.09.1999) SE(71) Applicant (for all designated States except US): GAM-  
BRO LUNDIA AB [SE/SE]; P.O. Box 10101, S-220 10  
Lund (SE).

(72) Inventors; and


(75) Inventors/Applicants (for US only): EDGSON, Ray-  
mond, Anthony [GB/GB]; Ramscroft, Malting Lane,  
Litlington, Nr. Royton (GB); DUNKLEY, Michael, John  
[GB/GB]; 20 Manhattan Drive, Cambridge CB4 1JL  
(GB); HAMMOND, Richard, J. [GB/GB]; 16 GrantaTerrace, Great Shelford, Cambridge CB4 3NF (GB).  
WILKINSON, Eric [GB/GB]; 14 Chequers Croft, Hilton,  
Cambridgeshire PE18 9PD (GB).(74) Agent: SPITMANN, Knut, H.; Gambro Patent Depart-  
ment, P.O. Box 10101, S-220 10 Lund (SE).(81) Designated States (national): AE, AL, AM, AT, AU, AZ,  
BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK,  
DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,  
IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU,  
LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT,  
RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA,  
UG, US, UZ, VN, YU, ZA, ZW.(84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian  
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European  
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,  
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,  
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

[Continued on next page]

(54) Title: METHOD AND CYCLER FOR PERITONEAL DIALYSIS



(57) Abstract: A method and a cycler intended for peritoneal dialysis, comprising a pressure chamber (201) provided with a first bag (202) for enclosing a fresh fluid intended to be filled to a patient and a second bag (203) for enclosing a spent fluid intended to be drained from a patient, said first and second bag being arranged at a weighing device (215) for weighing the combined weight thereof. A draining device is arranged for draining the spent fluid into the second bag supervised by the weighing device (215), and a replenishment device (204, 205, 206) is arranged for replenishing said first bag at a predetermined replenishment fluid flow rate during said draining step. Thus, time is saved and the peritoneal dialysis can be performed in a more efficient manner.

WO 01/19430 A1